



PRODUCT CATALOGUE

April 2023

MANUFACTURER

**SOLAR PANELS | SOLAR LIGHTS | LED LIGHTS
RENEWABLE PRODUCTS | SOLAR SYSTEM | ON GRID,
OFF GRID**



LED STREET LIGHT



TECHNICAL SPECIFICATION	
• HOUSING	Aluminium Die Cast With Powder Coated
• HOUSING FINISH	Black/Grey
• RATED LUMENS	160 Lm/W
• CONTROL GEAR	IP 66, 440V, OVP, UVP
• IP RATING	IP-66, IK-07
• CRI	>70
• SURGE PROTECTION	4 KV / As Per Required
• POWER FACTOR	>0.95
• INPUT VOLTAGE	85-285 V AC
• SYSTEM EFFICIENCY	(LM/W) >130
• COLOUR AVAILABLE	White/Warm White
• LED LIFE SPAN	50000 Hours
• LED BEAM ANGLE	120 Degree
• ELECTRICAL EFFICIENCY	>90%
• THERMAL EFFICIENCY	>90%

MODEL - STREET LIGHT LENS REGULER						
Wattage	24w	36W	50W	72W	100W	150W
Model Number	SLLR24	SLLR36	SLLR50	SLLR72	SLLR100	SLLR150
Standard Packing						



LED STREET LIGHT



TECHNICAL SPECIFICATION

• HOUSING	Aluminium Die Cast With Powder Coated
• HOUSING FINISH	Black/Grey
• RATED LUMENS	160 Lm/W
• CONTROL GEAR	IP 66, 440V, OVP, UVP
• IP RATING	IP-66, IK-07
• CRI	>70
• SURGE PROTECTION	4 KV / As Per Required
• POWER FACTOR	>0.95
• INPUT VOLTAGE	85-285 V AC
• SYSTEM EFFICIENCY	(LM/W) >130
• COLOUR AVAILABLE	White/Warm White
• LED LIFE SPAN	50000 Hours
• LED BEAM ANGLE	120 Degree
• ELECTRICAL EFFICIENCY	>90%
• THERMAL EFFICIENCY	>90%

MODEL - STREET LIGHT LENS ECO

Wattage	24w	36W	50W
Model Number	SLLE24	SLLE36	SLLE50
Standard Packing			



LED STREET LIGHT



TECHNICAL SPECIFICATION

• HOUSING	Aluminium Die Cast With Powder Coated
• HOUSING FINISH	Black/Grey
• RATED LUMENS	160 Lm/W
• CONTROL GEAR	IP 66, 440V, OVP, UVP
• IP RATING	IP-66, IK-07
• CRI	>70
• SURGE PROTECTION	4 KV / As Per Required
• POWER FACTOR	>0.95
• INPUT VOLTAGE	85-285 V AC
• SYSTEM EFFICIENCY	(LM/W) >130
• COLOUR AVAILABLE	White/Warm White
• LED LIFE SPAN	50000 Hours
• LED BEAM ANGLE	120 Degree
• ELECTRICAL EFFICIENCY	>90%
• THERMAL EFFICIENCY	>90%

MODEL -STREET LIGHT LENS QUIKY

Wattage	24w	36W	50W	100W
Model Number	SLLQ24	SLLQ36	SLLQ50	SLLQ100
Standard Packing				



LED STREET LIGHT



TECHNICAL SPECIFICATION	
• HOUSING	Aluminium Die Cast With Powder Coated
• HOUSING FINISH	Black/Grey
• RATED LUMENS	160 Lm/W
• CONTROL GEAR	IP 66, 440V, OVP, UVP
• IP RATING	IP-66, IK-07
• CRI	>70
• SURGE PROTECTION	4 KV / As Per Required
• POWER FACTOR	>0.95
• INPUT VOLTAGE	85-285 V AC
• SYSTEM EFFICIENCY	(LM/W) >130
• COLOUR AVAILABLE	White/Warm White
• LED LIFE SPAN	50000 Hours
• LED BEAM ANGLE	120 Degree
• ELECTRICAL EFFICIENCY	>90%
• THERMAL EFFICIENCY	>90%

MODEL - STREET LIGHT BACK CHOK							
Wattage	18W	24W	32W	50W	72W	100W	150W
Model Number	SLBC18	SLBC18	SLBC32	SLBC50	SLBC72	SLBC100	SLBC150
Standard Packing							



LED STREET LIGHT



TECHNICAL SPECIFICATION

• HOUSING	Aluminium Die Cast With Powder Coated
• HOUSING FINISH	Black/Grey
• RATED LUMENS	160 Lm/W
• CONTROL GEAR	IP 66, 440V, OVP, UVP
• IP RATING	IP-66, IK-07
• CRI	>70
• SURGE PROTECTION	4 KV / As Per Required
• POWER FACTOR	>0.95
• INPUT VOLTAGE	85-285 V AC
• SYSTEM EFFICIENCY	(LM/W) >130
• COLOUR AVAILABLE	White/Warm White
• LED LIFE SPAN	50000 Hours
• LED BEAM ANGLE	120 Degree
• ELECTRICAL EFFICIENCY	>90%
• THERMAL EFFICIENCY	>90%

MODEL - STREET LIGHT GLASS

Wattage	15W	24w	36W	50W
Model Number	OMSL15	OMSL24	OMSL36	OMSL50
Standard Packing				



LED STREET LIGHT



TECHNICAL SPECIFICATION

• HOUSING	Aluminium Die Cast With Powder Coated
• HOUSING FINISH	Black/Grey
• RATED LUMENS	160 Lm/W
• CONTROL GEAR	IP 66, 440V, OVP, UVP
• IP RATING	IP-66, IK-07
• CRI	>70
• SURGE PROTECTION	4 KV / As Per Required
• POWER FACTOR	>0.95
• INPUT VOLTAGE	85-285 V AC
• SYSTEM EFFICIENCY	(LM/W) >130
• COLOUR AVAILABLE	White/Warm White
• LED LIFE SPAN	50000 Hours
• LED BEAM ANGLE	120 Degree
• ELECTRICAL EFFICIENCY	>90%
• THERMAL EFFICIENCY	>90%

MODEL - STREET LIGHT LENS MS

Wattage	20W	30W	50W
Model Number	MS20	MS30	MS50
Standard Packing			

LED STREET LIGHT



TECHNICAL SPECIFICATION

• HOUSING	Aluminium Die Cast With Powder Coated
• HOUSING FINISH	Black/Grey
• RATED LUMENS	160 Lm/W
• CONTROL GEAR	IP 66, 440V, OVP, UVP
• IP RATING	IP-66, IK-07
• CRI	>70
• SURGE PROTECTION	4 KV / As Per Required
• POWER FACTOR	>0.95
• INPUT VOLTAGE	85-285 V AC
• SYSTEM EFFICIENCY	(LM/W) >130
• COLOUR AVAILABLE	White/Warm White
• LED LIFE SPAN	50000 Hours
• LED BEAM ANGLE	120 Degree
• ELECTRICAL EFFICIENCY	>90%
• THERMAL EFFICIENCY	>90%

MODEL - STREET LIGHT LENCY

Wattage	24w
Model Number	SLL24
Standard Packing	



LED STREET LIGHT



TECHNICAL SPECIFICATION

• HOUSING	Housing Poly Carbonate (PC)
• HOUSING FINISH	Black/Grey
• RATED LUMENS	160 Lm/W
• CONTROL GEAR	IP 66, 440V, OVP, UVP
• IP RATING	IP-66, IK-07
• CRI	>70
• SURGE PROTECTION	4 KV / As Per Required
• POWER FACTOR	>0.95
• INPUT VOLTAGE	85-285 V AC
• SYSTEM EFFICIENCY	(LM/W) >130
• COLOUR AVAILABLE	White/Warm White
• LED LIFE SPAN	50000 Hours
• LED BEAM ANGLE	120 Degree
• ELECTRICAL EFFICIENCY	>90%
• THERMAL EFFICIENCY	>90%

MODEL - STREET LIGHT STARK (PC)

Wattage	24W	30W
Model Number	SLS24	SLS24
Standard Packing		

LED STREET LIGHT



TECHNICAL SPECIFICATION

• HOUSING	Aluminium Die Cast With Powder Coated
• HOUSING FINISH	Black/Grey
• RATED LUMENS	160 Lm/W
• CONTROL GEAR	IP 66, 440V, OVP, UVP
• IP RATING	IP-66, IK-07
• CRI	>70
• SURGE PROTECTION	4 KV / As Per Required
• POWER FACTOR	>0.95
• INPUT VOLTAGE	85-285 V AC
• SYSTEM EFFICIENCY	(LM/W) >130
• COLOUR AVAILABLE	White/Warm White
• LED LIFE SPAN	50000 Hours
• LED BEAM ANGLE	120 Degree
• ELECTRICAL EFFICIENCY	>90%
• THERMAL EFFICIENCY	>90%

MODEL - STREET LIGHT LENS CANDY

Wattage	24w	36W	50W
Model Number	SLLC24	SLLC36	SLLC50
Standard Packing			



LED STREET LIGHT



TECHNICAL SPECIFICATION

• HOUSING	Aluminium Die Cast With Powder Coated
• HOUSING FINISH	Black/Grey
• RATED LUMENS	160 Lm/W
• CONTROL GEAR	IP 66, 440V, OVP, UVP
• IP RATING	IP-66, IK-07
• CRI	>70
• SURGE PROTECTION	4 KV / As Per Required
• POWER FACTOR	>0.95
• INPUT VOLTAGE	85-285 V AC
• SYSTEM EFFICIENCY	(LM/W) >130
• COLOUR AVAILABLE	White/Warm White
• LED LIFE SPAN	50000 Hours
• LED BEAM ANGLE	120 Degree
• ELECTRICAL EFFICIENCY	>90%
• THERMAL EFFICIENCY	>90%

MODEL - STREET LIGHT DOLPHIN REGULER

Wattage	25W	40W	80W
Model Number	DF25	DF40	DF80
Standard Packing			



LED STREET LIGHT



TECHNICAL SPECIFICATION

• HOUSING	Aluminium Die Cast With Powder Coated
• HOUSING FINISH	Black/Grey
• RATED LUMENS	160 Lm/W
• CONTROL GEAR	IP 66, 440V, OVP, UVP
• IP RATING	IP-66, IK-07
• CRI	>70
• SURGE PROTECTION	4 KV / As Per Required
• POWER FACTOR	>0.95
• INPUT VOLTAGE	85-285 V AC
• SYSTEM EFFICIENCY	(LM/W) >130
• COLOUR AVAILABLE	White/Warm White
• LED LIFE SPAN	50000 Hours
• LED BEAM ANGLE	120 Degree
• ELECTRICAL EFFICIENCY	>90%
• THERMAL EFFICIENCY	>90%

MODEL - STREET LIGHT DOLPHIN MAGNIFYING LENS

Wattage	75W	100W	200W
Model Number	DF75	DF100	DF200
Standard Packing			